

DC FAN

JAMICON®

92X92X25 mm

JF0925-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0925B1SR00	Dual Ball	12	10.2 ~ 13.8	60.19	0.189	3200	0.31	3.72	0.32	38.7	95
JF0925B1H-00				50.61	0.139	2800	0.25	3.00	0.35	35.1	
JF0925B1M-00				45.64	0.119	2500	0.17	2.04	0.20	32.1	
JF0925B1L-00				37.98	0.079	2100	0.13	1.56	0.16	26.9	
JF0925B1E-00				31.32	0.060	1700	0.09	1.08	0.10	21.8	
JF0925S1SR00	Sleeve			60.19	0.189	3200	0.31	3.72	0.32	38.7	
JF0925S1H-00				50.61	0.139	2800	0.27	3.24	0.35	35.1	
JF0925S1M-00				45.64	0.119	2500	0.17	2.04	0.20	32.1	
JF0925S1L-00				37.98	0.079	2100	0.13	1.56	0.16	26.9	
JF0925S1E-00				31.32	0.060	1700	0.09	1.08	0.10	21.8	
JF0925B2SR00	Dual Ball	24	20.4 ~ 27.6	60.19	0.189	3200	0.18	4.32	0.18	38.7	
JF0925B2H-00				50.61	0.139	2800	0.15	3.60	0.19	35.1	
JF0925B2M-00				45.64	0.119	2500	0.11	2.64	0.15	32.1	
JF0925B2L-00				37.98	0.079	2100	0.08	1.92	0.13	26.9	
JF0925B2E-00				31.32	0.060	1700	0.06	1.44	0.07	21.8	
JF0925S2SR00	Sleeve			60.19	0.189	3200	0.18	4.32	0.18	38.7	
JF0925S2H-00				50.61	0.139	2800	0.15	3.60	0.19	35.1	
JF0925S2M-00				45.64	0.119	2500	0.11	2.64	0.15	32.1	
JF0925S2L-00				37.98	0.079	2100	0.08	1.92	0.13	26.9	
JF0925S2E-00				31.32	0.060	1700	0.06	1.44	0.07	21.8	
JF0925B4H-00	Dual Ball	48	40.8 ~60.0	50.61	0.139	2800	0.09	4.32	0.09	35.1	
JF0925B4M-00				45.64	0.119	2500	0.08	3.84	0.08	32.1	
JF0925B4L-00				37.98	0.079	2100	0.06	2.88	0.06	26.9	
JF0925B4E-00				31.32	0.060	1700	0.05	2.40	0.05	21.8	

Specifications subject to change without notice

