


U5

Precision Devices Inc.

1-800-274-XTAL

INFO@PDIXTAL.COM



STANDARD QUARTZ CRYSTAL

The UM-5 series provides a broad range of frequencies, and a small profile, packaged in a robust, high reliability enclosure. The UM-5 has an extremely tight tolerance, and excellent mechanical characteristics.

ELECTRICAL PERFORMANCE (Ta=25°C)

Parameter	Standard Observed
Mechanical Shock	MIL-STD-202 Method 213, Condition C
Vibration	MIL-STD-202 Method 201, 204, and 214
Hermeticity	MIL-STD-202, Method 112
Solderability	IPC/EIA-STD-002A

PARAMETER	MINI-MUM	MAXI-MUM	UNITS
Center Frequency			MHz
Oscillation Mode	Fundamental, 3 rd , 5 th , and 7 th Overtone		
Maximum Series Resistance (See Note 3)			Ohms
Frequency Stability at +25°C (See Note 2) ±50.0ppm Typ.			ppm
Frequency Stability Over Temperature ±50.0ppm Typ.			ppm
Operating Temperature Range (See Note 2)			°C
Storage Temperature Range			°C
Drive Level	100.0uW		
Typical			
Seal Method	Resis-		
tance Weld			
Shunt Capacitance			pF
Motional Capacitance	Customer Request		
Load Capacitance			pF
Aging per year			ppm

