

Features


- ★ High-stability
- ★ Small package
- ★ Excellent environmental capability
- ★ Ideal for application to high-density circuit board
- ★ Suitable for small telecommunication equipment
- ★ Enable automatic mounting

Applications


- ★ Communication equipment
- ★ AV equipment
- ★ O A equipment
- ★ Measuring instruments




Dimension (Unit: mm)



Recommended Soldering (Unit: mm)



Frequency Vs Temperature



Specifications (Characteristics)

Item	Symbol	Specification
Normal Frequency	f	3.579 ~ 27.000 MHz
Frequency Tolerance at 25°C	$\Delta f/f$	±15, ±30, ±50 ppm
Frequency Stability (-10°C ~ +60°C)	$\Delta f/f$	±30, 50 ppm
Load Capacitance	CL	16.0pF
Operating Temp. Range	Topr	-40°C ~ +85°C
Storage Temp. Range	Tstg	-55°C ~ +125°C
Resistance of Series Resonance	Rs	3.579MHz ~ 4.499MHz : 150Ω MAX 4.500MHz ~ 4.999MHz : 130Ω MAX 5.000MHz ~ 6.999MHz : 120Ω MAX 7.000MHz ~ 9.999MHz : 100Ω MAX 10.000MHz ~ 11.999MHz : 80Ω MAX 12.000MHz ~ 13.999MHz : 70Ω MAX 14.000MHz ~ 15.999MHz : 50Ω MAX 16.000MHz ~ 27.000MHz : 35Ω MAX
Drive Level	PWR	10 ~ 50ΩW
Shunt Capacitance	C0	5.0pF Max.
Insulation Resistance	IR	500MΩ at DC100 V
Aging Level	fa	±5.0 ppm/yr MAX @ 25°C
Packing		Tape and Reel Package 2,000pcs per reel 10,000pcs per export carton

Part Number and Ordering

Part Number Code	Holder Type + Frequency + Tolerance + CL
Ordering Code	Same as Above
Example	ZM-309-3.579M-16P